



More than colour

CHROMATIC WEATHERGUARD

PRODUCT DESCRIPTION AND USES:

Chromatic Weatherguard is a premium quality pure acrylic latex emulsion paint designed for use on exterior surfaces. It is uniquely formulated to provide excellent weather-ability, easy application, resulting in a long lasting, uniform finish forming a breathable film that allows moisture vapour to pass through. It prevents the penetration of liquid water with a high resistance to blistering and peeling. It is a preferred product for high traffic areas like hotels, passage ways, high rise buildings, schools etc.

SURFACE PREPARATION:

New Plaster or Concrete
Surface must be clean, dry and free of loose material. Apply 01 coat of Chromatic Plaster Primer, followed by 02 coats of Chromatic Emulsion Undercoat ,then apply full 02 coats of Chromatic Weather guard, thinning down the first coat to allow maximum penetration. Allow 4 hours between coats.

Chalky/powdery or Flaking surfaces; Use stiff fiber or nylon brushes to remove all loose and friable materials. When the surface is clean, apply one liberal coat of Chromatic Acrylic Binder followed by two coats of Chromatic Weather guard. Allow 4 hours between coats.

Previously painted surfaces in sound condition ; Sand down the existing coat to a firm base. Then apply two coats of Chromatic Weatherguard. Allow 4 hours between coats.

FINISH:

Low sheen

APPLICATION:

By brush, roller or spray

THINING & MIXING:

Thin with tap water to the required consistency

EQUIPMENT CLEANING:

Clean equipment immediately after use with water

DRYING TIME:

Re-coatable after 4 hours

COLOUR RANGE:

Available in selected BS 4800 shades and over 3000 colours can be made on order.

SPREADING CAPACITY:

11-14 m²per litre at 40 microns DFT

PACK SIZES:

1 Litre, 4 Litres and 20 Litres

DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable.

No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond the control of Chromatic Paints Uganda.

Technology may change with time, necessitating changes to this Technical Data Sheet (TDS). Chromatic Paints Uganda reserves the right to amend the TDS without any further notice. It is the responsibility of the user to ensure that the latest TDS is being used for reference

For health & safety information, please refer to our Material Safety Data Sheet (MSDS)

